



**7/8" SDS-plus® Bulldog Rotary Hammer with Clic Loc
Model 11224VSRC**

Flexibility to work in a variety of materials
Features Clic Loc™ chuck change system
Maximum impact on many materials

Features:

- SDS-plus® bit system** tool-free bit changes with automatic bit locking, dust protection and maximum impact energy transfer rate
- Clic Loc™ Chuck Change System** Easily remove the SDS-plus® bit holder and snap on the included keyless carbide-tipped 3-jaw chuck
- Multi-function selector** 3 modes of operation, rotation only, rotary hammer and hammer only mode
- Variable-speed reversing trigger** for accurate bit starting, as well as removing fasteners or bound bits
- Vario-Lock™ positioning** rotates and locks chisel into 36 different positions to optimize working angle
- D-handle design** for extra control, ideal for overhead and downward drilling applications
- 360° Auxiliary handle with built-in depth gauge** wide range of movement along with consistent drilling depth
- Double insulated, UL listed, complies to OSHA**
- Integral clutch** helps minimize torque reaction

Includes:

- Auxiliary Handle -- 1 612 025 032
- Depth Gauge -- 1 613 001 010
- Carrying Case -- 2610994810
- 3-Jaw ClicLoc™ Chuck -- 1 618 572 000
- SDS-plus® ClicLoc™ Chuck -- 1 618 573 000

Specifications:

Model Number	11224VSRC
Amperage	6.9
Impact Energy (ft. lbs.)	1.6
No Load RPM	0-1,100
No Load BPM	0-6,150
Optimal Concrete Capacity Range	3/16" - 5/8"
Max. Hole Diameter in Concrete	7/8"
Max. Hole Diameter in Concrete-Thin Wall Core Bit	2-1/2"
Max. Hole Diameter in Steel	1/2"
Max. Hole Diameter in Wood	1"
Length	17-1/2"
Weight (lbs.)	6.5
Engineering Number	0611224739
Cord Length (ft.)	12
Rating	120V
Country Origin	Germany
Category	Rotary Hammers
Certifications	UL