



**1-9/16" SDS-max® Combination Hammer
Model 11240**

2 modes of operation - rotary hammer or hammer-only

Features

- SDS-max® bit system** tool-free bit changes with automatic bit locking, dust protection and maximum impact energy transfer rate
- "Combination" dual mode selector** 2 modes of operation, rotary hammer and hammer only mode
- Vario-Lock™ positioning** rotates and locks chisel into 12 different positions to optimize working angle
- Innovative service modules** designed so a qualified service technician can quickly replace the brushes and cord
- 360° Auxiliary handle** provides a wide range of movement along with operator comfort
- Integral clutch** helps minimize torque reaction
- Grounded design, UL listed, complies to OSHA**

Includes:

- Auxiliary Handle -- 2 602 025 062**
- Carrying Case -- 3 605 438 536**

Specifications

Model Number	11240
Amperage	10
Impact Energy (ft. lbs.)	5.2
No Load RPM	400
No Load BPM	3,000
Optimal Concrete Capacity Range	1/2 - 1-3/8
Max. Hole Diameter in Concrete	1-9/16
Max. Hole Diameter in Concrete-Core Bit	4
Max. Hole Diameter in Concrete-Thru Hole Bit	2-1/2
Length	17.25
Weight (lbs.)	13.2
Rating	120V

