



**1" SDS-plus® BULLDOG Xtreme Rotary Hammer
Model 11255VSR**

Outlasts the competition
The Fastest Longest Lasting Breed of Rotary Hammer
Maximum Speed, Maximum Life, Maximum Productivity

Features:

7.2 Amp; 0-1,300 RPM; 0-5,800 BPM

Multi-function Selector 3 modes of operation, rotation only, rotary hammer and hammer-only mode

Vario-Lock™ Positioning Rotates and locks chisel into 36 different positions to optimize working angle

Patented Rotating Brush Plate Provides equal power in forward and reverse

Patented Cord Turret 35° pivot for added flexibility and longer cord life

SDS-plus® Bit System Tool-free bit changes with automatic bit locking, dust protection and maximum impact energy transfer rate

Variable-speed Reversing Trigger For accurate bit starting as well as removing fasteners or bound bits

D-Handle design Ideal for overhead and downward drilling applications

Integral Clutch Helps minimize torque reaction

Includes:

Auxiliary Handle -- 2 602 025 141

Depth Gauge -- 1 613 001 010

Carrying Case -- 1 615 438 396

Specifications:

Model Number	11255VSR
Amperage	7.2
Impact Energy (ft. lbs.)	2.2
No Load RPM	0 - 1,300
No Load BPM	0 - 5,800
Optimal Concrete Capacity Range	3/16" - 5/8"
Max. Hole Diameter in Concrete	1"
Max. Hole Diameter in Concrete-Thin Wall Core Bit	2-5/8"
Max. Hole Diameter in Steel	1/2"
Max. Hole Diameter in Wood	3/4" - 1"
Length	17-1/4"
Weight (lbs.)	6.7
Engineering Number	0611255739
Bit Capacity	1" Solid Bit, 2-5/8" Thin Wall Core Bit
Rating	120V
Country Origin	Germany
Category	Rotary Hammers
Certifications	UL