



MOISTUREBLOC[®] LOW ODOR ADHESIVE REMOVER

Effectively Removes Flooring Adhesives

Meets USEPA AIM and OTC VOC regulations

DESCRIPTION

MoistureBloc Adhesive Remover strips adhesives from concrete floors and other concrete surfaces with relative ease. Removes many types of adhesives from concrete such as, cut back, latex and pressure sensitive. May not remove urethane and epoxy adhesives. The product will also clean oil stains from concrete. After use, Adhesive Remover is emulsifiable with water and general cleaners to yield a stripped concrete surface that is clean and ready for subsequent treatments. To remove coatings such as epoxys, sealers and curing compounds, use Vexcon's **Certi-Vex Concrete Stripper**.

APPLICATION

- Do not thin Adhesive Remover. It is supplied at the proper consistency for most effective action.
- Mix well prior to application to a uniform consistency.
- Apply Adhesive Remover with spray, roller or brush in a heavy application.
- Allow the material to soften the adhesive or to soak into oil stains on concrete but do not allow the surface to dry. Keep wet with Adhesive Remover.
- Once a gel has formed, remove the material and softened adhesive with a floor machine equipped with nylon bristle brush, steel wool, stone media or by scraping.
- During removal, apply additional Adhesive Remover to further soften the adhesive if necessary.
- Rinse area with water.
- Make a second application if needed. After removal of the adhesive, clean the surface with Vexcon's **Certi-Vex Super Degreaser & Cleaner**.
- Do a small test area prior to full adhesive application.
- Application Rate: 75-150 sq. ft. per gallon depending on thickness and type of adhesive to be removed.

PACKAGING

MoistureBloc Adhesive Remover is available in 55-gallon drums, 5-gallon pails and 1-gallon containers. Contact Vexcon to discuss your customized packaging requirements.

VITAL STATISTICS

- Flash Point: 109° F (43° C) minimum
- Boiling Point: 310-405° F (154-207° C)
- Autoignition Temp: 472° F (244° C)
- Extinguishing Media: Foams, Dry Chemical, CO₂, Water Fog, spray

HEALTH AND SAFETY

- Caution, slippery when applied. Use care when walking. Spread sand for traction.
- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.
- Aspiration of materials into the lungs can cause chemical pneumonitis, which can be fatal.
- Use of respirators is advised when using this product in confined areas.

The adhesive remover and/or materials may be classified as a hazardous material for purposes of disposal. This material should be kept in a separate container and local federal rules for disposal must be followed. Contact Vexcon if additional questions and/or information is required. Vexcon MSDS CP130 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product obtain a copy of the MSDS from your distributor or by contacting Vexcon Chemicals.

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly or our distributors.

- www.vexcon.com
- TechnicalService@vexcon.com
- CustomerService@vexcon.com
- Sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

SHELF LIFE

If properly stored in its original sealed container, three years from date of manufacture. May require mixing. Rotate your stock.