

**SPECIFICATION SHEET**  
**SPATTER-COTE 100 SPATTER PROTECTION**

Spatter-Cote 100 Spatter Protection provides for easy removal of concrete spatter from the back ends of ready mix trucks. Also effectively removes concrete spatter and build-up from tools, forms, screeds and other equipment. *Updated March 2005.*

**Environmental Report Card**

Non-carcinogenic.....Yes

Solventless.....Yes

**1. PRODUCT**

Spatter-Cote 100 Spatter Protection

**2. MANUFACTURER**

**Cresset Chemical Company, Inc.**

One Cresset Center, Box 367  
Weston, OH 43569

**3. PRODUCT DESCRIPTION**

**Basic Use:** Spatter-Cote 100 is applied to equipment surfaces exposed to concrete spatter. After use, simply clean the equipment by hosing off. Regular use keeps equipment clean and free from build-up.

Spatter-Cote 100 Spatter Protection:

- Easily rinses off with water
- Applies in hot or cold weather
- Applies by spray, brush or mop
- Does not promote corrosion
- Halts build-up before it starts
- Slowly removes build-up that is already there
- Aids in dirt and grease removal

Use Spatter-Cote 100 Spatter Protection on:

- Ready mix trucks
- Highway concrete paving equipment
- Portable batch plants
- Concrete tools and accessories
- Hard surface finishings during construction (windows, stairwells, etc.)
- Screeds
- Back side of forms
- "Dry mix" mixers

**Ground Shipping in the USA:** Containers holding 55 gallons or 5 gallons or less (regardless of quantity) are not federally regulated and shipping product in the Cresset package does not require following hazardous shipping requirements. Aerosols or a container holding 275

gallons or a bulk shipment requires federally mandated procedures on the driver, container and shipping papers. See Cresset brochure "Ground Shipping" for details.

#### 4. TECHNICAL DATA

Please see Tables.

#### TABLE OF PROPERTIES

	Aerosol	All Others	<b>Metric</b>
<b>Color</b>	Amber	Amber	Amber
<b>Opacity</b>	Clear	Clear	Clear
<b>Freeze Damage</b>	None	None	None
<b>Flash Point</b>	NA	150° F	65° C
<b>Viscosity (centipoises)</b>	NA	5 @ 68° F	5 @ 20° C
<b>Density</b>	7.2 lbs/gal	7.2 lbs/gal	861 g/L
<b>VOC (Volatile Organic Compounds)</b>	Exempt	245 g/L	245 g/L
<b>VOC (Volatile Organic Compounds)</b>	2.04 lbs/gal	3.59 lbs/gal	---

**Composition:** A proprietary mixture of corrosion inhibitors, mineral oil and emulsifiers. Contains no waxes, no silicones...no carcinogens.

#### COVERAGE WITH SPATTER-COTE 100

<u>Surface</u>	<u>(sq ft/gal)</u>	<u>(m2/l)</u>
Hard & Smooth	1,500	40

#### 5. APPLICATION

**Preparatory Work:** Equipment surfaces should be dry and free of loose dirt and dust. (Spatter-Cote 100 may be applied to surfaces with concrete build-up.)

**Regular Maintenance Program:** To keep the equipment clean apply Spatter-Cote 100 daily. Typically it is applied soon after hosing off the equipment.

Keeping new windows (and other fixtures) clean during construction: Apply Spatter-Cote 100 directly to windows and other hard surfaced items. If precipitation removes Spatter-Cote 100 simply re-apply it. Just hose off the windows in order to remove any spatter that collects on them. Do not let Spatter-Cote 100 collect on non-porous surfaces. When thoroughly hosed off windows, etc. it will not interfere with subsequent painting operations.

**Methods:** Apply Spatter-Cote 100 by spray, brush or roller to the equipment surface before being exposed to concrete spatter. Spatter-Cote 100 may be applied hours or up to 7 days before placing the equipment into service. To clean, hose the equipment surface protected by Spatter-Cote 100 with water. This will remove the concrete [spatter](#), dirt and grease. Once the equipment dries, recoat with Spatter-Cote 100.

Dilution with fuel oils, diesel fuel or water will reduce the product's effectiveness.

**Storage:** Spatter-Cote 100 Spatter Protection, in sealed containers, will keep indefinitely at temperatures from -20°F to 140°F (-30°C to 60°C). Section 1910.107 of "General Industrial Standards for Occupational Safety and Health" classifies Spatter-Cote 100 Spatter Protection as a 3A liquid for the purpose of meeting OSHA storage requirements.

**Precautions:** Keep out of reach of children. Avoid prolonged contact with the skin. Use with adequate ventilation. See Material Safety Data Sheet for additional safety information.

#### **6. AVAILABILITY AND COST**

**Availability:** Spatter-Cote 100 Spatter Protection is available in several different containers; Aerosol, 1 gallon, 5 gallon, orange and white 55 gallon drum and a disposable 275 gallon MegaPak. Contact Cresset Chemical Company for your nearest distributor.

**Cost:** The cost on hard, smooth surfaces is about \$0.014 per square foot (January 2001).

#### **7. LIMITED WARRANTY**

Cresset Chemical Company warrants the product against defects in materials for a period of 1 year from purchase. If Cresset receives notice of such defects during the warranty period, Cresset at its option will either replace the product or refund the purchase price. THE WARRANTY SET FORTH ABOVE IS EXCLUSIVE AND NO OTHER WARRANTY, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED. CRESSET SPECIFICALLY DISCLAIMS THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE REMEDIES PROVIDED HEREIN ARE BUYER'S SOLE AND EXCLUSIVE REMEDIES. IN NO EVENT SHALL CRESSET CHEMICAL COMPANY BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOSS OF PROFIT) WHETHER BASED ON CONTRACT, TORT OR ANY OTHER LEGAL THEORY.

#### **8. MAINTENANCE**

Not required.