

HAZARD RATING

4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0

MATERIAL SAFETY DATA SHEET
VEXCON NO. CC109



Performance Construction Chemicals

7240 STATE RD • PHILADELPHIA, PA 19135

VOICE: 215.332.7709 • FAX: 215.332.9997

TOLL FREE: 888-VEXCON-1

WEBSITE ADDRESS: www.vexcon.com

GENERAL INFORMATION

PRODUCT IDENTIFICATION: CERTI-VEX ENVIO® CURE WL

VOC CONTENT: 230 GR./LITER OR 1.92 #/GAL. **CATEGORY:** CURE

COMMON NAME: BOILED LINSEED OIL WITH PIGMENTS

DOT SHIPPING NAME: IN CONTAINERS LESS THAN 119 GALS:
 CERTI-VEX ENVIOCURE WL (NON-REGULATED)

IN CONTAINERS GREATER THAN 119 GALS: COMBUSTIBLE LIQUID,
 N.O.S. (STODDARD SOLVENT), 3, NA 1993, III

HEALTH AND SAFETY: THIS PRODUCT IS AN ORGANIC LIQUID AND
 WATER EMULSION. PER NFPA 30 THIS MIXTURE WITH A FLASH POINT
 GREATER THAN 200 F IS A CLASS III B COMBUSTIBLE LIQUID. ALL
 PRECAUTIONS PROVIDED ARE FOR THE ORGANIC LIQUID PORTION OF
 WHICH THIS PRODUCT MAY CONTAIN AS LITTLE AS 5%. USE WITH
 ADEQUATE VENTILATION. DO NOT INDUCE VOMITING IF SWALLOWED.
 USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER
 PROTECTIVE CLOTHING IS ADVISED WHEN HANDLING THIS PRODUCT.
 KEEP FROM FREEZING.

SECTION I

MANUFACTURER: VEXCON CHEMICALS
EMERGENCY NO.: 1-800-858-2828
CHEMTREC NO.: 1-800-424-9300
TELEPHONE NO 1-215-332-7700
ADDRESS: 7240 STATE RD., PHILA., PA 19135
PREPARED: FEBRUARY 1996
UPDATED: SEPTEMBER 13, 1999
PREPARED BY: DARRYL F. MANUEL/PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	CAS#	%	HAZARD DATA	UN#
PIGMENTS:				
1. TITANIUM DIOXIDE	13463-67-7	2%	RESPIRABLE DUST 5 mg/M3 TLV TOTAL DUST 10 mg/M3 TLV OSHA PEL: ACHIG 10 mg/M3 FOR DUST	
2. CALCIUM CARBONATE	1317-65-3	6%	SAME AS ABOVE (TOTAL DUST)	
LINSEED OIL	8001-26-1	25%	ND	
EMULSIFIERS		3%	ND	
DRIERS	8032-32-4	2%	ND	
H2O		62%	ND	

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 760 mm Hg 105° C **MELTING POINT:** N/A
SPECIFIC GRAVITY (H2O=1): .93 **VAPOR PRESSURE:**
VAPOR DENSITY (AIR=1): 4.9
SOLUBILITY IN H2O % BY WT: 100% SOLUBLE
% VOLATILES BY VOL: 46%
EVAPORATION RATE (BUOH=1): 1
PH (AS IS): 9.0-10.0 **PH (1% SOLN):** 7.5
APPEARANCE AND ODOR: TAN COLORED RESIN EMULSION
(ETHER=1): 9.5 LESS THAN ETHER

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT: (TEST METHOD): >200° F TCC
AUTOIGNITION TEMPERATURE: ND
FLAMMABLE LIMITS IN AIR: % BY VOL:
LOWER: ND **UPPER:** ND
EXTINGUISHING MEDIA: FOAM, WATER, FOG OR SPRAY.
SPECIAL FIRE FIGHTING PROCEDURES: THE USE OF SELF CONTAINED
 BREATHING APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS. WATER
 MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIA, BUT HELPFUL IN
 KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING
 LIQUID WITH WATER USED FOR COOLING PURPOSES. VAPOR IS HEAVIER
 THAN AIR.
UNUSUAL FIRE AND EXPLOSION HAZARD: PRODUCT WILL BURN IF
 TEMPERATURE EXCEED BOILING POINT. POLYMER FILM ARE CAPABLE OF
 BURNING, GIVING OFF OXIDES OF CARBON.

SECTION V REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: PRODUCT IS STABLE
INCOMPATIBILITY: THIS PRODUCT IS INCOMPATIBLE WITH STRONG
 OXIDIZING AGENTS. STRONG ACIDS OR BASES AND SELECTED AMINES
HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION IN
 THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON
 DIOXIDE.
CONDITIONS CONTRIBUTING TO HAZARD POLYMERIZATION:
 N/A WILL NOT OCCUR.

SECTION VI HEALTH HAZARD INFORMATION

ROUTES OF EXPOSURE:

INHALATION: INHALATION OF HIGH VAPOR CONCENTRATIONS MAY HAVE RESULTS RANGING FROM DIZZINESS AND HEADACHES TO UNCONSCIOUSNESS.

SKIN CONTACT: THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.

SKIN ABSORPTION: SEE ABOVE

EYE CONTACT: THIS PRODUCT MAY BE AN EYE IRRITANT

INGESTION/INHALATION: TLV 50-100 PPM ESTIMATED FROM SIMILAR PRODUCTS NOTE: THE THRESHOLD LIMIT VALUE (TLV) OF 100 ppm VAPOR IN AIR HAS BEEN ESTABLISHED BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS FOR STODDARD SOLVENT AND IS THUS APPLICABLE TO MINERAL SPIRITS IN A RECENT STUDY OF EXXON CORP. MEDICAL RESEARCH WITH LABORATORY ANIMALS (RATS) EXPOSED TO VAPORS IN AIR OF A SOLVENT SIMILAR TO MINERAL SPIRITS KIDNEY DAMAGE WAS NOTED IN MALE RATS AT THIS CONCENTRATION. THE RECENT STUDY SUGGESTS THAT THIS OCCUPATIONAL EXPOSURE LIMIT MAY HAVE TO BE LOWERED FOR THIS PRODUCT. WORK IS CONTINUING TO VALIDATE THESE FINDINGS AND DETERMINE WHETHER REVISED OCCUPATIONAL EXPOSURE LIMIT SHOULD BE RECOMMENDED FOR MINERAL SPIRIT.

ACUTE OVEREXPOSURE: MODERATELY IRRITATING ON SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEFAT THE SKIN POSSIBLY CAUSING DERMATITIS.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES CONSULT A PHYSICIAN.

SKIN: IMMEDIATELY WASH SKIN WITH SOAP AND PLENTY OF WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN.

INGESTION: DO NOT INDUCE VOMITING, SEEK PROMPT MEDICAL ATTENTION.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

AQUATIC TOXICITY (E.G. 96 HR. TLM):

WASTE DISPOSAL METHOD: TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA OR STATE REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT. TYPICALLY, CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE. STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES, INCLUDING PILOT LIGHT ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP IS COMPLETE. STOP SPILL AT SOURCE. DIKE SPILL AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVEL INTO CONTAINERS.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES

INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY(SPECIFY IN DETAIL): CHEMICAL CARTRIDGE RESPIRATOR; HALF MASK ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

EYES: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION, OR INJURY.

GLOVES: IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR VP.

OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS ARE RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS: PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE RE-USE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

OTHER HANDLING AND STORAGE REQUIREMENTS: STORE IN WELL VENTILATED AREA. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

HMS HAZARD RATINGS:

	NPCA-HMIS	NFPA 704	KEY
HEALTH	1	1	4=SEVERE
FLAMMABILITY	1	1	3=SERIOUS
REACTIVITY	0	0	2=MODERATE
			1=SLIGHT
			0=MINIMAL

ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL IT'S INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

PREPARED BY: DARRYL MANUEL

TITLE: PRESIDENT

COMPANY: VEXCON CHEMICALS

ADDRESS: 7240 STATE RD. PHILA., PA 19135

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETION OF THE INFORMATION CONTAINED HEREIN