



Performance Construction Chemicals

CERTI-VEX[®] CONCRETE STRIPPER VERTICAL

Heavy Bodied Concrete Stripper used to remove coatings
Meets EPA and AIM VOC Regulations

DESCRIPTION

CERTI-VEX CONCRETE STRIPPER VERTICAL is a scientifically formulated heavy bodied concrete stripper, having a light grease consistency, especially designed for the cleaning and the removal of coatings and other residues from vertical surfaces with relative ease. Use **Certi-Vex[®] Concrete Stripper** for horizontal applications. After use, Certi-Vex Concrete Stripper Vertical is emulsifiable with water and general cleaners to yield a stripped concrete surface that is clean and ready for subsequent treatments.

APPLICATION

Scrape or brush the surface to be stripped with a wire brush or broom to remove loose and flaking coating or residual dirt. Apply Certi-Vex Concrete Stripper Vertical with airless spray, roller or brush in a heavy application. Allow the stripper to soften the coating but do not allow the surface to dry. Keep wet with Certi-Vex Concrete Stripper Vertical. Once a gel has formed, remove the stripper and softened coatings with a rotary machine equipped with plastic, steel or wool or by scraping or brushing. During removal, apply Certi-Vex Concrete Stripper Vertical to further soften the coating. Make a second application if needed. After removal of the coating, clean the surface with pine oil cleaner and water. Apply a test patch prior to completely coating the surface. Do not thin Certi-Vex Concrete Stripper Vertical; it is supplied at the proper consistency for most effective action. Application Rate: 75-150 sq.ft. per gallon depending on thickness and type of coating to be removed.

PACKAGING

Certi-Vex Concrete Stripper Vertical is available in 55-gallon drums, 5-gallon pails and 1-gallon units. Contact Vexcon directly to discuss your customized packaging requirements.

VITAL STATISTICS

- Flash Point: 140° F (60° C) TCC
- Boiling Point: 310-428° F (154-220° C)
- Autoignition Temp: ND
- Extinguishing Media: Foams, Dry Chemical, CO₂, Water fog or spray

HEALTH AND SAFETY

- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.
- Aspiration of materials into the lungs can cause chemical pneumonitis, which can be fatal.
- Use of respirators is advised when using this product in confined areas.

The stripper solution and/or materials may be classified as a hazardous material for purposes of disposal. This material should be kept in a separate container and local federal rules for disposal must be followed. Contact Vexcon if additional questions and/or information is required. Vexcon MSDS #OP102 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product, it is advisable to get a copy of the MSDS from your distributor or by contacting Vexcon Chemicals.

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly or our distributors.

- www.vexcon.com
- TechnicalService@vexcon.com
- CustomerService@vexcon.com
- Sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

SHELF LIFE

If properly stored in its original sealed container, three years from date of manufacture. Rotate your stock