

Paver Renew™

Rejuvenates and protects your concrete pavers

PAVER RENEU VERTICAL STAIN WATER BASE SEAL & PROTECT • DECORATIVE • REVITALIZE

DESCRIPTION

Paver Renew Vertical Stain Water Base is a ready to use water based colored curing and sealing compound that quickly forms a decorative, hard, dustproof, water repellent, chemical resistant protective film on new and existing vertical concrete surfaces. This film hardens to a wear resistant sealer that enhances and revitalizes the appearance of new or existing architectural concrete. Provides protection from moisture, deicing salts, staining and other harmful environmental elements. Paver Renew Vertical Stain Water Base is a breathable coating and will not whiten when moisture is present. It can also be applied immediately after proper preparation to new pavers, concrete and masonry surfaces. Recommended for use on vertical walls and architectural sections.

BENEFITS

- Easy to use
- Available in 5 attractive colors
- Easy re-coat
- Low odor
- No waiting, apply immediately
- Resistant to yellowing and color fading
- Greater long-term resistance
- Corrects color variations
- Extends life and appearance
- Apply to damp surfaces without loss of adhesion
- Seals and hardens surface reducing clean up and maintenance costs
- Excellent protection against staining, attack by alkali, oil, cleaners and common industrial chemicals
- Prevents efflorescence, dusting and spalling

SURFACE PREPARATION

New surfaces should be clean of all foreign materials such as oil, grease, asphalt, mud and powdery substances. Remove efflorescence using **Paver Renew Etch & Efflorescence**

Remover. On old or existing masonry or concrete surfaces where there is loose scaly residue, sandblasting or wire brushing may be necessary. Small cracks, voids and blemishes may be filled by troweling **Certi-Vex® Patch RTU** with a large flat bladed spatula. Large holes and damaged areas should be repaired by grouting or trowel filling with **Certi-Vex® Patch**.

APPLICATION

- Product is supplied at the proper consistency for application and dilution will reduce efficiency.
- Thoroughly mechanically mix before applying.
- Apply by low-pressure high solids commercial grade solvent resistant sprayer. The sprayer must be clean and dry. If cleaning with solvents is required, use **Certi-Vex Equipment Cleaner** and flush thoroughly with water before use. Clean sprayer as directed between applications to ensure best results. If sprayer is not available, use a brush or ¼" roller.
- If applying by roller, do not over-work material. Do not back roll or allow the working area to dry, coat in one direction only.
- When roller applying, roller should be dampened with water prior to use. Keep roller wet with material. Do not allow roller to dry.
- When spray applied, particular care must be taken with spray overlap area. Proper technique for spraying calls for a pattern which prevents run down of material.
- The sealer can be applied to damp or new surfaces, as long as there are no slick water surface spots visible.
- A uniform appearance requires even coats leaving no gaps. Some areas may be more porous than others; these areas may require additional coats to even out the appearance. Caution: Do not over-apply material. See Special Notes section.
- Apply first coat at a rate of 250-300 sq.ft./gal (6.2-7.5 m²/L). A second coat is recommended for long term durability and to even out color. See Second Coat section.

SPECIAL NOTES

- To assist in application please note, 200 sq.ft. /gallon is equal to the thickness of a sheet of paper
- Will cause bleeding of bituminous surfaces
- For vertical application only – Use **Paver Renew Concrete Stain** for horizontal surfaces
- Application of more than two coats is not recommended
- Over application may lead to surface discoloration and improper sealer performance
- Protect all areas from over spray.
- Do not allow sealed area to become wet until dry. See dry times.
- Do not apply more material per square foot than specified
- Can apply when surface temperatures are 40° F - 85° F. When below or above these ranges review Vexcon's Cold and Hot Weather Application Guides
- Same lot numbers should be used throughout the project. If lots differ, box mix prior to applying.
- Mix well before use
- Keep from freezing
- If properly stored in its original sealed container, two years from date of manufacture. Rotate your stock

SECOND COAT

After application of the first coat, a second coat may be applied when the surface has dried.

Apply second coat as directed at 400-500 sq.ft. /gal (10-12.5 m²/L).

MAINTENANCE

Sealed areas should be cleaned regularly, use **Paver Reneu Degreaser & Cleaner** for all cleaning requirements. Periodic reapplication may be required as the sealer wears off.

SPECIFICATIONS/COMPLIANCE

- ASTM C 309, Type II, Class A&B
 - ASTM C 1315, Type II, Class B
 - Federal specification TT-C-800-A (GSA-FSS) Type II.
 - USDA approved
 - Meets EPA & AIM VOC regulations: 250 gr./liter or 2.09 #/gal. – Cure
- Test reports and certifications are available upon request

PACKAGING

Paver Reneu Vertical Stain Water Base is available in 55-gallon drums, 5-gallon pails and 1-gallon containers.

PHYSICAL PROPERTIES

- Color 5 standard colors
- Dry - tack free 45 minutes
- Solids 25% minimum

HEALTH AND SAFETY

- Use only with adequate ventilation
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting
- Use of respirators is advised when using in confined areas.

Vexcon MSDS #PV140 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this product, it is advisable to obtain a copy of the MSDS # PV140 from your distributor or by contacting Vexcon.

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly or your local Paver Reneu dealer.

- www.vexcon.com
- Technicalservice@vexcon.com
- Customerservice@vexcon.com
- Sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

WARRANTY

Vexcon warrants that the goods supplied hereunder shall be of its standard quality and shall conform in all material respects to the sample which has been made available for testing by buyer prior to sale. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OR NEGLIGENCE, GROSS NEGLIGENCE, STRICT LIABILITY OR ANY OTHER TORT. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES. No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.