

Paver Reneu™

Rejuvenates and protects your concrete pavers

PAVER RENEU STRIPPER

Heavy Bodied Concrete Stripper used to remove Sealers, Coatings and Oil Stains
Meets EPA and AIM VOC regulations

DESCRIPTION

PAVER RENEU STRIPPER strips pavers, concrete floors and other concrete surfaces with relative ease. Removes many types of coatings from concrete such as sealers, curing compounds, urethanes, epoxies in addition to floor waxes and adhesives. It also cleans oil stains from concrete. After use, Paver Reneu Stripper is emulsifiable with water and general cleaners to yield a stripped surface that is clean and ready for subsequent treatments. Use **Paver Reneu Stripper Vertical** for vertical applications.

APPLICATION

Scrape or brush the surface to be stripped with a wire brush or broom to remove loose and flaking coating or residual dirt. Mix well prior to application to a uniform consistency. Apply Paver Reneu Stripper with spray, roller or brush in a heavy application. Allow the stripper to soften the coating or to soak into oil stains but do not allow the surface to dry. Keep wet with Paver Reneu Stripper. Once a gel has formed, remove the stripper and softened coatings with a floor machine equipped with plastic, steel wool or stone media or by scraping or brushing. During removal, apply Paver Reneu Stripper to further soften the coating. Make a second application if needed. After removal of the coating, clean the surface with **Paver Reneu Degreaser & Cleaner**. Prior to application, apply to a small area as a test to determine proper application technique and rate of material required. Do not thin Paver Reneu Stripper. It is supplied at the proper consistency for most effective action. Application Rate: 75-150 sq. ft. per gallon depending on thickness and type of coating to be removed.

PACKAGING

Paver Reneu Stripper is available in 55-gallon drums, 5-gallon pails and 1-gallon containers.

VITAL STATISTICS

- Flash Point: 140° F (60° C) TCC
- Boiling Point: 310-428° F (154-220° C)
- Autoignition Temp: ND
- Extinguishing Media: Foams, Dry Chemical, CO₂, Water fog or spray.

HEALTH AND SAFETY

- Caution, slippery when applied. Use care when walking. Spread sand for traction.
- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.
- Aspiration of materials into the lungs can cause chemical pneumonitis, which can be fatal.
- Use of respirators is advised when using this product in confined areas.

The stripper solution and/or materials may be classified as a hazardous material for purposes of disposal. This material should be kept in a separate container and local federal rules for disposal must be followed. Contact Vexcon if additional questions and/or information is required. Vexcon MSDS # PV152, is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product, it is advisable to obtain a copy of the MSDS # PV152, from your distributor or by contacting Vexcon.

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly or your local Paver Reneu dealer.

- www.vexcon.com
- TechnicalService@vexcon.com
- CustomerService@vexcon.com
- Sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

SHELF LIFE

If properly stored in its original sealed container, three years from date of manufacture. May require mixing. Rotate your stock.

WARRANTY

Vexcon warrants that the goods supplied hereunder shall be of its standard quality and shall conform in all material respects to the sample which has been made available for testing by buyer prior to sale. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OR NEGLIGENCE, GROSS NEGLIGENCE, STRICT LIABILITY OR ANY OTHER TORT. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES. No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.