

# BLOCK FILL GROUT (COARSE)

## Description

ProSpec<sup>®</sup> Block Fill Grout Coarse is a mixture of portland cement, sand, gravel and additives.

## Features

- Pumpable
- Requires only the addition of water
- Meets requirements of ASTM C 476 Standard Specification for Masonry type fine grout

## Uses

- Grouting cavities in masonry units
- Filling any space where a structural fill is required
- Grouting spaces behind door jambs

## Technical Data

Compressive Strength ASTM C 476

28 days

3,000 psi (20.1 MPa)

Slump

10 inches (254 mm)

## Mixing

Mix 80 lb. (36.3 kg) bag with approximately 5.5 quarts (5.2 L) of water or until a pancake batter like consistency is achieved. Do not over water; this may lead to segregation.

## Placement

Pour the grout quickly and continuously into area to be filled. Light rodding will help consolidate grout and eliminate air bubbles.

## Curing

No special curing required.

## Best Performance

- The cavities to be filled should be free of any matter that is deleterious to portland cement products or from any materials that may decompose over time such as wood, foam, paper or organic material.
- When filling masonry units, DO NOT allow wall to reach a height that grout will not be able to completely fill the lower units.
- Do not retemper

## Coverage

80 lb. (36.3 kg) bag will fill slightly more than two 16" blocks. One bag yields 0.7 cu. ft. (0.02 cu. m).

# BLOCK FILL GROUT (COARSE)

## Packaging

80 lb. (36.3 kg) bag

## Shelf Life

One year from date of manufacture.

## Caution

KEEP OUT OF REACH OF CHILDREN AND ANIMALS.

**WARNING! CAUSES IRRITATION.** Wear protective clothing and equipment. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in

irritation of the skin, eyes or nasal passages from alkali in Portland cement. When wet, contact with the skin or eyes may result in irritation or burns.

**WARNING! HARMFUL IF INHALED** - Avoid breathing dust. Keep container closed. Use with adequate ventilation. Excessive

exposure by inhalation over an extended period of time may result in the development of pulmonary diseases including pneumoconiosis and silicosis. Crystalline Silica has been classified by IARC and NTP as a carcinogen.

## First Aid

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water. If irritation persists, get medical attention.

Refer to the MSDS for full information.

For additional information, call Bonsal American at 704-525-1621 or CHEMTREC at 800-424-9300 or 703-527-3887 outside of the USA.

LIMITED 1 YEAR WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal American's option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAL AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES INCLUDING LOSS OF PROFITS OF ANY KIND.

Product demonstrations are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. This Warranty constitutes the sole warranty given by Bonsal American in connection with this product. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American. Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

ProSpec<sup>®</sup> is the registered trademark of Sakrete of North America.  
8201 Arrowridge Blvd. Charlotte, NC 28273 • www.prospec.com • E-Mail: prospec@oldcastleapg.com