

# Rufco-Wrap Seaming Tape

# #RWS165

**DIRECTIONS:** Rufco-Wrap Seaming Tape #RWS165 is a very strong white polypropylene tape. The bond strength of the cold weather acrylic adhesive system will actually increase with time. It is specially formulated to have excellent performance characteristics at sub freezing temperatures along with a quick tack for ease of installation.

**APPLICATIONS:** RWS165 is used primarily as a seaming tape for Rufco-Wrap housewrap and other insulation sheathing materials. It can be used to repair rips, punctures or tears in sheathing and housewrap products. RWS165 can be applied to corners, joints, sill plates etc., to improve air tightness.

Properties	Imperial	Metric
Thickness Mil (nominal)	3.00 Mil (.003")	0.076 mm
Adhesion (Peel): Rufco-Wrap Stainless Steel	28.0 oz/in 64.8 oz/in	30.65 N/100 mm 47.10 N/100 mm
Tensile	20 lbs./inch width	350.2 kPa
Elongation	136%	136%
Size	1 7/8 inches x 165 feet	47.6 mm x 50.3 m

**SHELF LIFE:** Recommend one year from date of receipt by customer when stored under optimum conditions. (70° F, 50% RH)

Note: To the best of our knowledge, these are the typical property values and are intended as guides only, not as specification limits. RAVEN INDUSTRIES MAKE NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO; no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage.

## SALES OFFICE

P.O. BOX 5107  
Sioux Falls, SD 57117-5107  
(605) 335-0174  
(605) 331-0333 FAX  
**800-635-3456**

## PLANT LOCATIONS

Sioux Falls, South Dakota  
Springfield, Ohio



**RAVEN**  
INDUSTRIES