

HAZARD RATING

4=EXTREME
 3=HIGH
 2=MODERATE
 1=SLIGHT
 0=INSIGNIFICANT

HEALTH	3
FLAMMABILITY	2
REACTIVITY	0

MATERIAL SAFETY DATA SHEET
VEXCON NO. PV152

Performance Construction Chemicals

7240 STATE RD • PHILADELPHIA, PA 19135
 VOICE: 215.332.7709 • FAX: 215.332.9997
 TOLL FREE: 888-VEXCON-1
 WEBSITE ADDRESS: www.vexcon.com

GENERAL INFORMATION

PRODUCT IDENTIFICATION: PAVER RENEU STRIPPER
VOC CONTENT: NOT REQUIRED **CATEGORY:** NOT REQUIRED
COMMON NAME: SOLVENT CONCRETE STRIPPER
DOT SHIPPING NAME: IN CONTAINERS LESS THAN 119 GALS:
 CERTI- VEX CST (NON REGULATED) IN CONTAINERS GREATER THAN
 119 GALS: COMBUSTIBLE LIQUID, N.O.S. (PINE OIL).3. NA 1993, III
FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT: RESIN SOLUTION,
 FLAMMABLE, 3, UN1866, III
HEALTH AND SAFETY: COMBUSTIBLE LIQUID: USE ONLY WITH
 ADEQUATE VENTILATION I F SWALLOWED, DO NOT INDUCE VOMITING:
 USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER
 PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT.

SECTION I

MANUFACTURER: VEXCON CHEMICALS
EMERGENCY NO: 1-800-858-2828
CHEMTREC NO: 1-800-424-9300
TELEPHONE NO: 1-215-332-7709
ADDRESS: 7240 STATE RD., PHILA., PA. 19135
PREPARED: FEBRUARY 1999
UPDATED: APRIL 2005
PREPARED BY: DARRYL F. MANUEL/PRESIDENT

SECTION II HAZARDOUS INGREDIENTS

<u>MATERIAL OR COMPONENTS</u>	<u>CAS. NO.</u>	<u>HAZARD DATA</u>	<u>UN#</u>
PINE OIL	8002-09-3	NOT ESTB.	1272
ETHYLENE GLYCOL MONOPROPYLETHER	0020807-30-9	OSHA HAZARD COMBUSTIBLE 100 PPM	1268
AR-100 SILICA AMORPHOUS, FUMED	64742-95-6 112945-52-5	OSHA 15 mg/M3 TOTAL DUST 5 m/M3 RESPIRABLE DUST	

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT, 760 mm Hg: 310-428° F **MELTING POINT:** N/A
SPECIFIC GRAVITY 0.92 **VAPOR PRESSURE:** 1.5 mm Hg @20C
VAPOR DENSITY (AIR=1): 4.0 **SOLUBILITY IN H2O % BY WT:** MISCABLE
EVAPORATION RATE (BUOH=1): .1PH (AS IS): 8.8 **PH (1% SOLN):**
APPEARANCE AND ODOR: PALE YELLOW LIQUID WITH SWEET PINE ODOR

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT: (TEST METHOD): 140° F TCC
AUTOIGNITION TEMPERATURE: ND
FLAMMABLE LIMITS IN AIR: % BY VOL: ND **LOWER:** 0.7 **UPPER:** 6.0
EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL, CO2, WATER FOG OR
 FIRE FIGHTING: USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES
 AND TO PROTECT PERSONNEL. ISOLATE "FUEL" SUPPLY FROM FIRE. USE
 FOAM, DRY CHEMICAL, OR WATER SPRAY TO EXTINGUISH FIRE. AVOID
 SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO
 DANGER OF BOIL OVER. THE USE OF SELF-CONTAINED BREATHING
 APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS. SEE ALSO SECTION
 IX.

GENERAL HAZARD: COMBUSTIBLE LIQUID, CAN FORM COMBUSTIBLE
 MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC
 DISCHARGE, MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN
 CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS
 RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE
 DANGEROUS. DO NOT PRESSURIZE, CUT WELD, BRAZE, SOLDER DRILL
 GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC
 ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND
 CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY
 DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM
 RECONDITIONER ,OR PROPERLY DISPOSED OF.

ELECTROSTATIC ACCUMULATION HAZARD: USE PROPER GROUNDING
UNUSUAL FIRE AND EXPLOSION HAZARD KEEP WORK AREAS FREE OF
 HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.

SECTION V REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: PRODUCT IS STABLE
INCOMPATIBILITY: THIS PRODUCT IS INCOMPATIBLE WITH STRONG
 OXIDIZING AGENTS. STRONG ACIDS OR BASES AND SELECTED AMINES.
HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION IN
 THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON
 DIOXIDE.
CONDITIONS CONTRIBUTING TO HAZARD POLYMERIZATION: N/A WILL
 NOT OCCUR.

SECTION VI HEALTH HAZARD INFORMATION

INGESTION/INHALATION: TLV 50-100 ppm ESTIMATED FROM SIMILAR PRODUCTS

ACUTE OVEREXPOSURE: ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS; MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.

SKIN: WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.

INHALATION: MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. DISPOSAL OF RESIDUAL MATERIAL, EITHER IN LIQUID FORM OR ABSORBED WITH CLAY OR SAND, MUST BE DONE IN COMPLIANCE WITH WITH EPA, STATE, AND LOCAL REGULATIONS.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

LAND SPILL: ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL, IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS IMPLEMENT CLEANUP PROCEDURES: FOR LARGE SPILL IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST .RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

WATER SPILL: REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSENTS MAY BE USED IN ON-CONFINED WATERS. CONSULT AN EXPERT DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

SECTION VIII CONTROL MEASURES

VENTILATION REQUIREMENTS LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY (SPECIFY IN DETAIL): CHEMICAL CARTRIDGE RESPIRATOR; HALF MASK ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

EYES: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

GLOVES: IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

OTHER CLOTHING AND EQUIPMENT :TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS ARE A RECOMMENDATION WHEN WORKING WITH THIS PRODUCT. AVAILABILITY OF EYE WASHES & SAFETY SHOWERS IWORK

AREAS IS RECOMMENDED.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS:

FIRE FIGHTING: WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIA BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE REMOVE SATURATED CLOTHING AND FLUSH AFFECTED AREAS WITH WATER.

OTHER HANDLING AND STORAGE REQUIREMENTS: KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION EQUIVALENT TO FRESH AIR.

HMIS HAZARD RATINGS: THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NEPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

HMIS HAZARD RATINGS:

	NPCA-HMIS	NFPA 704	KEY
HEALTH	3	3	
4=SEVERE			
FLAMMABILITY	2	2	3=SERIOUS
REACTIVITY	0	0	
2=MODERATE			
	1=SLIGHT		0=MINIMAL

SECTION X REGULATORY INFORMATION

TSCA: THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN VARIABLE COMPOSITION BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 80541-3.

CERCLA: IF THIS PRODUCT IS ACCIDENTALLY SPILLED, IT IS NOT SUBJECT TO ANY SPECIAL REPORTING UNDER THE REQUIREMENTS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA). WE RECOMMEND YOU CONTACT LOCAL AUTHORITIES TO DETERMINE IF THERE MAY BE OTHER LOCAL REPORTING REQUIREMENTS.

SARA TITLE III: UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPER FUND AMENDMENTS AND REAUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES.

DELAYED HEALTH, FIRE.

THIS PRODUCT DOES NOT CONTAIN SECTION 313 REPORTABLE INGREDIENTS.

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL IT'S INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT NVENTORY OF CHEMICAL SUBSTANCES? YES

PREPARED BY: DARRYL MANUEL

TITLE: PRESIDENT

COMPANY: VEXCON CHEMICALS

ADDRESS: 7240 STATE RD., PHILA., PA. 19135

THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN