

**HAZARD RATING**

4=EXTREME  
 3=HIGH  
 2=MODERATE  
 1=SLIGHT  
 0=INSIGNIFICANT

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>REACTIVITY</b>	<b>0</b>

**MATERIAL SAFETY DATA SHEET**  
**VEXCON NO. PS105-500**



**VEXCON**  
**CHEMICALS**

The road to better performance <sup>TM</sup>

7240 STATE RD • PHILADELPHIA, PA. 19135

VOICE: 215.332.7709 • FAX: 215.332.9997

TOLL FREE: 888-VEXCON-1

WEBSITE ADDRESS: [www.vexcon.com](http://www.vexcon.com)

**GENERAL INFORMATION**

**PRODUCT IDENTIFICATION:** CERTI-VEX ENVIO WATERPROOF 500

**VOC CONTENT:** 250 GRAMS/LITER OR 2.07 #/GAL.

**CATEGORY:** WATER REPELLANT

**COMMON NAME:** ALKOXYSILANE, EMULSION

**DOT SHIPPING NAME:** IN CONTAINERS GREATER THAN AND LESS THAN 119 GALS: CERTI-VEX ENVIO WATERPROOF 500 (NON-REGULATED)

**HEALTH AND SAFETY** COMBUSTIBLE LIQUID: THIS PRODUCT IS A SOLVENT H2O EMULSION. ALL PRECAUTIONS PROVIDED ARE FOR THE SOLVENT PORTION OF WHICH THIS CONTAINS LESS THAN 20%: COMBUSTIBLE LIQUID: USE ONLY WITH ADEQUATE VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE CLOTHING IS ADVISED WHEN HANDLING THIS PRODUCT: FLASH POINT: SOLVENT H2O EMULSION 157 DEGREES F (NON-FLAMMABLE)

**SECTION I**

**MANUFACTURER:** VEXCON CHEMICALS  
**EMERGENCY NO.:** 1-800-858-2828  
**CHEMTREC NO.:** 1-800-424-9300  
**TELEPHONE NO.:** 1-215-332-7709  
**ADDRESS:** 7240 STATE RD., PHILA., PA. 19135  
**PREPARED:** FEBRUARY 1996  
**UPDATED:** NOVEMBER 2000  
**PREPARED BY:** DARRYL F. MANUEL

**SECTION II HAZARDOUS INGREDIENTS**

<u>MATERIAL OR COMPONENTS</u>	<u>CAS. NO.</u>	<u>%</u>	<u>HAZARD DATA</u>
OCTYLTRIETHOXYSILANE	2943-75-1	10%	NONE ACGIH-TLV NONE ND
EMULSIFIERS UNIDENTIFIED SILOXANE IMPURITIES	NONE	2%	NOT ESTABLISHED
WATER		88%	

**SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS**

**BOILING POINT,** 210 F      **MELTING POINT:** N/A  
**SPECIFIC GRAVITY (H2O=1)** 0.98      **VAPOR PRESSURE:** NA  
**VAPOR DENSITY (AIR=1):** >1      **VOLATILES BY VOL:** 100%  
**SOLUBILITY IN H2O % BY WT:** 100%  
**EVAPORATION RATE (BUOH=1):** 0.12      PH (AS IS): 5-6      pH (1% SOLN): NA  
**APPEARANCE AND ODOR:** WATER WHITE TO YELLOW EMULSION.

**SECTION IV FIRE AND EXPLOSION DATA**

**FLASH POINT:** (TEST METHOD): 212° F TAG CLOSED CUP

**AUTOIGNITION TEMPERATURE:** 472

**FLAMMABLE LIMITS IN AIR: % BY VOL:** ND

**LOWER:** ND      **UPPER:** ND

**EXTINGUISHING MEDIA:** REGULAR FOAM, CARBON DIOXIDE OR DRY CHEMICAL. WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES

**FIRE HAZARDS: FLAMMABLE** VAPORS MAY ACCUMULATE IN THE CONTAINER HEADSPACE ON FORMATION OF HYDROLYSIS BY-PRODUCTS.

**SPECIAL FIRE FIGHTING PROCEDURES: THE** USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE- DEMAND OR OTHER POSITIVE PRESSURE MODE. UNUSUAL FIRE AND EXPLOSION HAZARD: VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK.

**SECTION V REACTIVITY DATA**

**CONDITIONS CONTRIBUTING TO INSTABILITY:** PRODUCT IS STABLE.

**INCOMPATIBILITY:** THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS STRONG ACIDS OR BASES AND SELECTED AMINES.

**HAZARDOUS DECOMPOSITION PRODUCT** THERMAL DECOMPOSITION IN THE PRESENCE OF AIR YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, SI02 ACETALDEHYDE AND HYDROCARBON VOLITILES.

**CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR.

**SECTION VI HEALTH HAZARD INFORMATION**

**HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR**

**CLASSIFICATION SOURCE**

**ROUTES OR EXPOSURE/INHALATION:** THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTHEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPORCONCENTRATION.

**SKIN CONTACT:** THIS PRODUCT MAY RESULT IN SKIN IRRITATION UPON PROLONGED/REPEATED CONTACT.

**SKIN ABSORPTION:** SEE ABOVE

**EYE CONTACT:** THIS PRODUCT MAY BE AN EYE IRRITANT.

**INGESTION:** SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

**EFFECTS OF OVEREXPOSURE TLV-50 PPM**

**ACUTE OVEREXPOSURE: ANESTHESIA,** HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

**EMERGENCY AND FIRST AID PROCEDURES:**

**EYES:** FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.

**SKIN:** WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.

**INHALATION:** MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.

**INGESTION:** DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

**SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE**

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, STATE, AND LOCAL REGULATIONS.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

**LAND SPILL:** ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS IMPLEMENT CLEANUP PROCEDURES: FOR LARGE SPILL IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

**WATER SPILL:** REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSENTS MAY BE USED IN ON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

**SECTION VIII CONTROL MEASURES**

**VENTILATION REQUIREMENTS:** LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME- WEIGHTED TLV RANGES. IF GENERAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY (SPECIFY IN DETAIL):** THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF A OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIRPACK.

**EYE:** CHEMICAL GOGGLES AND/OR FACE SHIELDS ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

**GLOVES:** THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS.

**OTHER CLOTHING AND EQUIPMENT:** IMPERMEABLE APRONS AND HELMETS (HEAD COVER) ARE ADVISED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

**SECTION IX SPECIAL PRECAUTIONS**

**PRECAUTIONARY STATEMENTS: FIRE FIGHTING: WATER** MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIA BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE REMOVE SATURATED CLOTHING AND FLUSH AFFECTED AREAS WITH WATER.

**OTHER HANDLING AND STORAGE REQUIREMENTS: KEEP** PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION EQUIVALENT TO FRESH AIR.

**HMS HAZARD RATINGS:**

THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMS) NATIONAL FIRE PROTECTION ASSOCIATION (NEPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

	NPCA-HMS	NFPA 704	KEY
HEALTH	2	2	4=SEVERE
FLAMMABILITY	1	1	3=SERIOUS
REACTIVITY	1	1	2=MODERATE
			1=SLIGHT
			0=MINIMAL

**SECTION X REGULATORY INFORMATION**

**TSCA:** THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6.

**CERCLA:** IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 800-424-8802. THE REPORTABLE SPILL QUANTITY OF THIS PRODUCT IS 5,000 POUNDS. DELAYED HEALTH, FIRE.

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

**PREPARED BY:** DARRYL MANUEL  
**TITLE:** PRESIDENT  
**COMPANY:** VEXCON CHEMICALS  
**ADDRESS:** 7240 STATE ROAD, PHILA. PA. 19135

**THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN**