

MATERIAL SAFETY DATA SHEET

SECTION I – PRODUCT IDENTIFICATION

TRADE NAME: RE-DO-IT PRIMER

CHEMICAL FAMILY: ETHYLENE/VINYL ACETATE COPOLYMER

**MANUFACTURER: STAMPCRETE INTERNATIONAL, LTD, 325 COMMERCE BLVD.,
LIVERPOOL, NY 13088**

EMERGENCY PHONE: (800) 233-3298

SECTION II – HAZARDOUS INGREDIENTS

DESCRIPTION	CAS#	PERCENT	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE (MM HG)
			TLV	PEL	
ETHYLENE VINYL (NONE) (PROPRIETARY) *		49-59	NON HAZARDOUS*		
PROPYLENE GLYCOL	57-55-6	3-5	50 PPM		
WATER		41-44			

*Product may contain trace amounts of residual vinyl acetate. Keep levels below 10ppm.

DOT – NOT REGULATED – Liquid synthetic plastics, NOT.

SECTION III – PHYSICAL DATA

BOILING POINT (F)	212F	SPECIFIC GRAVITY (H2O=1)	1.060
VAPOR PRESSURE (mmHg)	17 @ 20C	% VOLATILE BY VOLUME (5)	46.5%
VAPOR DENSITY (AIR=1)	0.62	EVAPORATION RATE	1
SOLUBILITY IN WATER:	MISCIBLE		

APPEARANCE & ODOR: MILK WHITE AQUEOUS EMULSION, SWEET ODOR

SECTION IV – FIRE & EXPLOSION HAZARD DATA

FLASH POINT: NON-FLAMMABLE

FLAMMABLE LIMITS: NONE

EXTINGUISHING MEDIA: WATER, FOG, FOAM, ALCOHOL FOAM, CO2, DRY
CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: NO SPECIAL PROCEDURES REQUIRED

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE EXPECTED

SECTION V – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 50PPM

