

# GILSONITE OVERDRIVE® DRIVEWAY SEALER

PRODUCT DATA

## DESCRIPTION

A premium asphalt driveway coating/sealer formulated from special refined asphalts, quick drying solvents, and select durable Gilsonite resins to provide long lasting preventative maintenance for driveways, playgrounds, and recreational surfaces. Dries to a shiny black finish. Gilsonite resin based formula.

## USES

Preventative asphalt driveway surface maintenance. Use to recoat and seal the surface of your driveway, or recreational surface where a shiny black finish is desired.

## APPLICATION

Prepare the surface to receive the GILSONITE OVERDRIVE® Coating by trimming grass, weeds, or bushes away from the driveway surface and sweep clean. Surface should be thoroughly dry and free of dust and debris. Remove oil or grease spots with detergent and water. Allow time to dry. Ensure the surface is thoroughly dry prior to application. Fill cracks over 1/4" wide with OVERDRIVE Crack Filler or OVERDRIVE Rubberized Crack Filler. After preparing surface, stir product thoroughly to assure even consistency. Do not heat. Do not thin. Use directly from pail. Pour a ribbon of material across the surface. Using a stiff-bristle brush or heavy-nap roller apply as thinly as possible, being careful to work the product to penetrate the driveway surface and into fine cracks or pores. Spread the material at the rate of 1 gallon per 125 to 150 square feet. Do not allow excessive accumulation in low spots, as drying will be inhibited. Upon completion, fine sand may be sprinkled onto the wet coating to enhance skid resistance. Foot traffic and vehicle traffic may be allowed after the coating has dried for 24 hours after application. Keep the container tightly closed when not in use. Dries to a shiny black finish. Clean tools thoroughly with mineral spirits in a well-ventilated outdoor area after use.

## TYPICAL PHYSICAL PROPERTIES\*

Weight Per Gallon, Lbs.	8.0
Cure Time (at recommended coverages)	4-8 hrs to set, 24 hrs

\*All values stated as nominal



## NOTES AND PRECAUTIONS

Contains mineral spirits and is a combustible material. Keep away from heat, sparks, and open flame. Not compatible with coal tar sealers. Do not apply on surfaces previously sealed with coal tar emulsion. For use only on asphalt surfaces. Newly laid asphalt pavement should cure for six months or at least one summer. Driveway Sealer is not to be used for repairing large cracks or broken pavement. DO NOT APPLY in damp weather, if rain is imminent, or if temperature is below 40°F. Apply only in well-ventilated area.

Central District	220 West 4th Street, Joplin, Missouri 64801
Northeast District	4500 Tamko Drive, Frederick, Maryland 21701
Southeast District	2300 35th Street, Tuscaloosa, Alabama 35401
Southwest District	7910 South Central Expressway, Dallas, Texas 75216
Western District	5300 East 43rd Avenue, Denver, Colorado 80216

800-641-4691
800-368-2055
800-228-2656
800-443-1834
800-530-8868

www.tamko.com

For Technical Services call 1-800-641-4691

**TAMKO**®  
ROOFING PRODUCTS