

EXPRESS RM CALCIUM CHLORIDE

Product Data Sheet

General Description

EXPRESS RM calcium chloride (CaCl_2) is a white, premium anhydrous, high purity mini-pellet with 94 to 97 weight percent CaCl_2 .

EXPRESS exhibits the following features and benefits:

- It is fast dissolving,
- It is low dusting,
- It is a free flowing pellet, and
- It contains very low levels of impurities.

Applications

EXPRESS RM calcium chloride is also suitable for ready mix concrete acceleration, dust stabilization on unpaved roads, tire weighting, brine refrigeration, and non-potable water treatment, and has other industrial and commercial applications.

Availability

EXPRESS PACKAGING

Package	Pallet Size	Units/ Pallet	Pallets/ Truckload
40lb Plastic Bag	40x48	56	15

TETRA Chemicals

25025 Interstate 45 North, Suite 600
The Woodlands, Texas 77380

Phone: 281.367.1983

Customer Service: 800.327.7817

Fax: 281.298.7150

www.tetrachemicals.com

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.

Safety and Handling

EXPRESS RM calcium chloride when in solution is a strong salt solution. Protective clothing, rubber gloves and eye protection are recommended. Rubber safety boots should also be worn in work areas, since calcium chloride can damage leather. This product should be handled in areas with proper ventilation. Before using this product, refer to the MSDS (available on the Company's website) for complete safety and handling guidelines. For proper disposal guidelines for calcium chloride wastes, consult the appropriate local regulatory authorities.

CHEMICAL PROPERTIES

Chemical	CaCl_2
Appearance	White mini-pellet
Odor	None
Assay	94%-97% by weight CaCl_2
Bulk Density	Approx. 55 lbs/cubic foot
pH	7.0 to 10.0

TYPICAL ANALYSIS*

Calcium Chloride	≤ 94% by weight
Alkali Chlorides (as NaCl)	< 1% by weight
Total Magnesium (as MgCl_2)	< 0.1% by weight
Other Impurities (not H_2O)	< 1% by weight
Iron (Fe)	< 20 mg/kg
Sodium (Na)	< 500 mg/kg
Sulfates (as SO_4)	< 250 mg/kg
Alkalinity (as CaCO_3)	< 2,000 mg/kg

*impurities based on 100% CaCl_2 basis

TYPICAL SCREEN ANALYSIS

Screen Number:	
4 (4.76 mm)	100% passing by weight
8 (2.38 mm)	80-100% passing by weight
40 (0.42 mm)	0-5% passing by weight