



CERTI-VEX ENVIO[®]ASSIST

EVAPORATION REDUCER

VOC CONTENT: 0-CURE

DESCRIPTION

CERTI-VEX ENVIOASSIST is an evaporation retardant that is applied to the concrete surface during finishing to extend working time and assist in concrete slab finishing. Proper use of **CERTI-VEX ENVIOASSIST** will reduce early evaporation between the various placing and finishing operations, which is a major cause of plastic shrinkage cracking.

ADVANTAGES

- Extends finishing time
- Reduces moisture evaporation due to wind and sunlight
- Meets VOC requirements
- Economical concentrate
- Easy to use, just mix with water

MATERIAL DILUTION INSTRUCTION

CERTI-VEX ENVIOASSIST is supplied as a 9:1 concentrate. In a clean container, add 9 parts water and 1 part **CERTI-VEX ENVIOASSIST**. Mix the container prior to use with a mechanical drum mixer for 15 minutes. Do not dilute less or more than 9 parts water: 1 part concentrate.

APPLICATION

Apply **CERTI-VEX ENVIOASSIST** as required to extend concrete slab finishing. Prior to application follow directions in MATERIAL DILUTION INSTRUCTION Section. Apply by sprayer immediately after placement and first screeding of the concrete. Apply at 200-sq. ft./gal. (5.0 M²/L). Repeat spraying procedure as required in localized areas due to premature setting.

PROTECT FROM FREEZING

CERTI-VEX ENVIOASSIST is supplied as an oil-in-water emulsion. Not recommended for use at temperatures below 40° F (4° C). Keep from freezing and do not store outside in the winter months.

TOPCOATS AND ADHESIVES

CERTI-VEX ENVIOASSIST is not a curing compound. After concrete finishing a curing compound, like **CERTI-VEX ENVIO[®] CURE**, or a cure and seal like, **VEXCON STARSEAL[®]**, should be applied.

SPECIAL NOTES

- Vexcon Chemicals is available to provide assistance in the proper use of this product, including dilution.
- Customer assumes responsibility of proper dilution of product in accordance with instructions provided.
- Our laboratory is available to test retains prior to usage of **CERTI-VEX ENVIOASSIST** and blended water.
- Failure to follow all instructions may cause product not to perform as anticipated. Seller will have no liability in that event.
- To clean equipment: When wet or dry, use water
- Fugitive dye available upon request
- Can apply to 40⁰F

PACKAGING

CERTI-VEX ENVIOASSIST is available in 55-gallon drums and 5-gallon pails. Contact Vexcon directly to discuss your customized packaging requirements.

VITAL STATISTICS

- Flash Point: NA
- Boiling Point: 212° F (100° C)

HEALTH AND SAFETY

- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.
- Use of respirators is advised when using in confined areas.

Vexcon MSDS # CC113 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product it is advisable to obtain a copy of the MSDS, #CC113, from your distributor or by calling Vexcon Chemicals at 888-839-2661.

THIS PRODUCT INCLUDES

Water
Non Hazardous Materials

DOT Shipping Name: **CERTI-VEX ENVIOASSIST**
(Non-Regulated)
Common Name: Wetting Agent Emulsion

CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly or our distributors. **CERTI-VEX ENVIOASSIST** is available at stocking distributors nationwide.

- www.vexcon.com
- Technicalservice@vexcon.com
- Customerservice@vexcon.com
- Sales@vexcon.com
- Voice: 888.839.2661
- Fax: 215.332.9997

SHELF LIFE

If properly stored in its original sealed container, one year.
Rotate your stock.